

MTP-15-Series-R410A R32 R290 R454C All in One Air to Water Heat Pump

Model		MAR-3W/150	MAR-3W/200	MAR-3W/250	MAR-3W/150B	MAR-3W/200B	MAR-3W/250B
Product Code							
Power supply		220~240V,50Hz			220~240V,50Hz		
Refrigerant		R410a or R32			R290/R454C		
Ambient temp		-25 °C - 43°C					
Heating water range		20°C — 55°C					
Heating1 (A+20°C W15°C/W55 °C)	Capacity	KW	2.60	2.60	2.60	2.60	2.60
	Power Input	KW	0.62	0.62	0.62	0.62	0.62
	COP	W/W	4.19	4.19	4.19	4.19	4.19
Dimension	mm	640*640*1550	640*640*1850	640*640*2150	640*640*1550	640*640*1850	640*640*2150
Water Tank Volume	L	150	200	250	150	200	250
Backup Electric Heater	KW	1.5(Optional)			1.5(Optional)		
Inlet/Outlet Connect Size		DN25	DN25	DN25	DN25	DN25	DN25
Net/Gross Weight	kg	57.0	67.0	82.0	57.0	67.0	82.0
Design Pressure	MPa	4.2	4.2	4.2	4.2	4.2	4.2
Noise Level(1 M)	dB(A)	≤53.0	≤55.0	≤55.0	≤53.0	≤55.0	≤55.0

Model		MAR-3W/150C	MAR-3W/200C	MAR-3W/250C	
Product Code					
Power supply		220~240V,50Hz			
Refrigerant		R134A			
Ambient temp		-25 °C - 43°C			
Heating water range		20°C — 75°C			
Heating1 (A+20°C W15°C/W55 °C)	Capacity	KW	2.60	2.60	2.60
	Power Input	KW	0.62	0.62	0.62
	COP	W/W	4.19	4.19	4.19
Dimension	mm	640*640*1550	640*640*1850	640*640*2150	
Water Tank Volume	L	150	200	250	
Backup Electric Heater	KW	1.5(Optional)			
Inlet/Outlet Connect Size		DN25	DN25	DN25	
Net/Gross Weight	kg	57.0	67.0	82.0	
Design Pressure	MPa	4.2	4.2	4.2	
Noise Level(1 M)	dB(A)	≤53.0	≤55.0	≤55.0	

Picture



Note:

The above designs and specifications might be changed without prior notice for product improvement